

7.1 Ezi CERAMIC TILE CLEANER



PRODUCT INFORMATION

EZI CERAMIC TILE CLEANER Name

Packing 1 Ltrs. 4 Ltrs

Shelf Life 12 Months in Dry Condition **Light Yellowish Liquid** Appearance

1.00 to 1.50 pH Value

Inflammability

APPLICATION DATA

Mixing Ratio

For Light Duty 1 pbw. Ezi CERAMIC TILE CLEANER to

6 pbw. Water

For Medium Duty 1 pbw. Ezi CERAMIC TILE CLEANER to

3 pbw. Water

1 pbw. Ezi CERAMIC TILE CLEANER to For Heavy Duty

3 pbw. Water

COMPANY INFORMATION

MANUFACTURED BY: Ezi MOTARTECH SDN. BHD. (874800-D)

FACTORY ADDRESS

:1888, Jalan Lahar Bubu, Kepala Batas, 13200, Pulau Pinang. PENANG

: PT990, 2 ½ KM Jln Off Simpang Pulai-Lahat, **IPOH**

31300 Kampung Kepayang, Perak Darul Ridzuan.

SALES OFFICE

L +604-658 8817 PENANG = +604-658 8818 **\$\&\ +605-357 5818** = +605-357 5818 **IPOH** : 📞 +602-6277 3709 = +603-6272 3760

Ezi TECHNICAL ADVISORY CENTRE

\$\&\ +6012-431 8221 ★ technical@ezi-fix.com

For more information please log on to: www.ezi-fix.com

DESCRIPTION

Ezi CERAMIC TILE CLEANER is a ready to use, acid-based cleaning agent for removing cement, adhesive, grout residues and common dirt at wall and floor ceramic tiles, sanitary wares and etc.

USAGE

Suitable to use for:

- Removal of cement stains.
- Removal of adhesive and grout residues.
- Removal dirts at wall and floor ceramic tiles.
- Removal dirts at sanitary wares.

Important Note:

Ensure that Ezi CERAMIC TILE CLEANER does not use on certain types of surfaces:

- Metal
- Highly polished surface
- Porcelain tile
- Marble
- Decorative tiles and etc.

INSTRUCTIONS

- (A) Shake well the Ezi CERAMIC TILE CLEANER before using.
- (B) Dilute the product in accordance to recommended mixing ratio.
- (C) Apply Ezi CERAMIC TILE CLEANER onto stained areas with brush or cloth and leave it for 5 to 15 minutes for reaction to take place.

Note: Do not leave longer than 15 minutes before washing off to avoid potential damange to those surfaces.

(D) Wash it off thoroughly with clean water.

- Do not use on tiling where adhesive bed or grout has not set.
- Advisable to do a trial on a small areas to determine ease of compatibility before actual application commences.

MATERIAL SAFETY INFORMATION

A mildly corrosive material. Keep out of chidren reach. Avoid inhalation, ingestion and avoid from entering eyes. Prolonged contact with unprotected parts of body should be avoided. For more details, please refer to Ezi Material Safety Data Sheet.

When working with this product, recommended to follow the safety precaution below.







GLOVES



SHOES





This product is manufactured by Ezi MOTARTECH SDN. BHD. certified to ISO 9001: 2015 Quality Management System by Business Systems Certification Australia. www.ezi-fix.com TDS 7.1 Rev. 01